



SPECIFICATION, INSTALLATION AND OPERATION SHEET



- Aluminum DOGIPOT® Pet Sign, with mounting hardware (two (2) 2¼" x ¼" tap bolts, washers and locknuts)
- Aluminum DOGIPOT[®] MINI JUNIOR Bag Dispenser (ITEM #1002M-2) or Poly JUNIOR Bag Dispense (ITEM #1007-2) with mounting hardware
- Two (2) keys for Dispenser locking access panel
- Two (2) rolls of SMART DOGIPOT[®] Litter Pick Up Bags (ITEM #1402) (200 count per roll), installed in DOGIPOT[®] JUNIOR Bag Dispenser

SEPARATE SHIPPING BOX

 2" x 2" x 4' - 8' Galvanized Steel Telescopic Mounting Post, with installation hardware (two (2) carriage bolts (2½" x 5/16"), washers and locknuts)

PLEASE CHECK THE ABOVE INVENTORY AND CALL YOUR DISTRIBUTOR IF ANY PARTS ARE MISSING.



INSTALLATION AND OPERATION INSTRUCTIONS

- Select a good visible spot in your community or park where you want to install the DOGIPOT® QUIK Pet Station.
- 2. Prior to installation, remove the 1¾" x 1¾" x 4' portion of the mounting post from the 2" x 2" x 4' portion of the mounting post before cementing. Insert the larger portion of the mounting post (2" x 2" x 4') approximately 14" into an 18" deep by 8" diameter hole filled with a 40 lb. bag of "ready to use" concrete mix. To stabilize the post while cementing, place a rod, bolt or other device through the two bottom holes, prior to inserting into the ground and cementing. Level the post in a straight vertical position and let concrete dry for at least 12 hours.
- 3. After the concrete is dry, insert the smaller portion of the post (1¾" x 1¾" x 4") into the larger cemented portion of the post (2' x 2' x 4') until the the first 4 holes are lined up between the two posts. Use two (2) carriage bolts, washers and locknuts to fix the telescopic post in position, the upper bolt in the top overlapping hole, pointing from right to left and the lower bolt in the bottom overlapping hole, pointing from front to back. The total height above ground with both post parts should now be approximately 6"6".
- 4. Start by installing the **DOGIPOT®** Pet Sign on top of the 1¾" post, with the upper hole matching the most upper hole in the square post using the enclosed 2¾" bolts, washers and locknuts. Continue installing the Aluminum or Poly **DOGIPOT®** JUNIOR Bag Dispenser according to the mounting instructions enclosed with the Dispenser, ensuring that he upper edge of the Dispenser is approximately **1" below** the lower edge of the **DOGIPOT®** Pet Sign.
- 5. ENJOY WATCHING PET OWNERS PICK UP AFTER THEIR DOGS!

SPECIFICATION, INSTALLATION AND OPERATION SHEET (A) DOGIPOT® PET SIGN (ITEM #1203 / 1204) PET WASTE TRANSMITS DISEASE • H: 18" x W: 11.5" 14 gauge reflective aluminum LEASH AND CLEAN UP AFTER Weight: 1.35 lbs. YOUR PET Forest green on white (B DOGIPOT® JUNIOR BAG DISPENSER 400 bag capacity THIS AREA Two diamond shaped bag dispenser slots CLEAN Locking access panel Clearly posted instructions DOGK POT (C) TELESCOPIC GALVANIZED STEEL MOUNTING POST (ITEM #1301-P) 2" x 2" x 8' 11 gauge galvanized steel Weight: 15 lbs. TOTAL HEIGHT FROM ABOVE GROUND: • 6'.6" SPACE BETWEEN DISPENSER AND SIGN: • 1.0" HOLE: • D: 18.0" x W: 8.0" Fill with 40 lbs. "ready to use" cement (MOUNTING HARDWARE INCLUDED)